

# GH HILCOFLEX AGRO EXTRA SUPER HEAVY

## AGRICULTURAL HOSE WITH RUBBERIZED LINING AND JACKET

### MATERIAL CONSTRUCTION

#### Jacket lining:

- Warp: High-tenacity polyester, reinforced design
- Weft: Polyamide/polyester, circular woven
- The special jacket construction ensures outstanding adhesion, tight bending radii and much lower pressure loss compared to a 100% polyester jacket lining
- Very little elongation under pressure thanks to a special weaving and vulcanization process
- Totally embedded in the rubber, offering optimum protection against mechanical damage

#### Rubberized lining and jacket:

- Very high-grade NBR/PVC compound, extruded through the weave in a special one-step production process
- Special additives in the compound guarantee outstanding resistance to aging and ozone
- Inside: Very smooth for minimal pressure loss
- Outside: Reinforced cover and strong longitudinal ribs for extremely high abrasion resistance

### ADVANTAGES

- ✓ Unbeatable resistance to aging and ozone
- ✓ Outstanding abrasion resistance, even on difficult ground surfaces
- ✓ Very good resistance to fertilizers, agricultural chemicals and microorganisms
- ✓ Very high tensile strength, low pressure loss and elongation
- ✓ Excellent adhesion between the rubber and jacket lining
- ✓ Tough and durable

### AT A GLANCE

#### Standard lengths

- 100 m
- 200 m

**i** Other lengths available on request (possibly with cutting fee)

#### Temperature ranges

-20 °C bis 80 °C

(Specifications apply to Water)

#### Standard colors

black

#### Areas of application

- Irrigation, especially pivot systems
- Liquid manure distribution
- Sludge and wastewater distribution
- Transport hose for watering and drainage
- For especially heavy-duty work

### CONTACT

Gollmer & Hummel GmbH  
Gässlesweg 23  
75334 Straubenhardt

**T** +49 (0) 7082 9434-0

**F** +49 (0) 7082 9434-99

**E** [info@gollmer-hummel.de](mailto:info@gollmer-hummel.de)

## PRESSURES

### Working pressure:

Specifications apply only to the hose (medium water, 20 °C). The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly. For compressed air, the maximum working pressure is 25% of the burst pressure.

### Maximum working pressure:

Approval can only be given by the manufacturer upon clarification of the exact area of application.

[Order hose sample >>](#)

## DATASHEET

Inside diameter in mm	Weight in g/m	Wall thickness in mm	Working pressure in bar	Max. working pressure in bar	Burst pressure in bar	Tensile strength in kg
127	2100	4.5	15	18	45	17,000
150	2700	4.5	14	17	42	17,900

**i** Specifications apply only to the hose. The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly.

PRODUCT IMAGES

