

# GH HILCOFLEX AGRO

## AGRICULTURAL HOSE WITH RUBBERIZED LINING AND JACKET

### MATERIAL CONSTRUCTION

#### Jacket lining:

- Warp: High-tenacity polyester, reinforced design
- Weft: Polyamide/polyester; circular woven
- The special jacket construction ensures outstanding adhesion, tight bending radii and much lower pressure loss compared to a 100% polyester jacket lining
- Very little elongation under pressure thanks to a special weaving and vulcanization process
- Totally embedded in the rubber, offering optimum protection against mechanical damage

#### Rubberized lining and jacket:

- Very high-grade NBR/PVC compound, extruded through the weave in a special one-step production process
- Special additives in the compound guarantee outstanding resistance to aging and ozone
- Inside: Very smooth for minimal pressure loss
- Outside: Reinforced cover and strong longitudinal ribs for extremely high abrasion resistance

### ADVANTAGES

- ✓ Unbeatable resistance to aging and ozone
- ✓ Outstanding abrasion resistance, even on difficult ground surfaces
- ✓ Very good resistance to fertilizers, agricultural chemicals and microorganisms
- ✓ Very high tensile strength, low pressure loss and elongation
- ✓ Excellent adhesion between the rubber and jacket lining
- ✓ Tough and durable

### AT A GLANCE

#### Standard lengths

- 100 m
- 200 m

**i** Other lengths available on request (possibly with cutting fee)

#### Temperature ranges

-20 °C bis 80 °C

(Specifications apply to Water)

#### Standard colors

black

#### Areas of application

- Irrigation, especially pivot systems
- Liquid manure distribution
- Sludge and wastewater distribution
- Transport hose for watering and drainage
- For especially heavy-duty work

### CONTACT

**Gollmer & Hummel GmbH**  
Gässlesweg 23  
75334 Straubenhardt

**T** +49 (0) 7082 9434-0

**F** +49 (0) 7082 9434-99

**E** [info@gollmer-hummel.com](mailto:info@gollmer-hummel.com)

PRESSURES

Working pressure:

Specifications apply only to the hose (medium water, 20 °C). The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly. For compressed air, the maximum working pressure is 25% of the burst pressure.


Maximum working pressure:

Approval can only be given by the manufacturer upon clarification of the exact area of application.

Order hose sample >>

DATASHEET METRIC

Inside diameter in mm	Weight in g/m	Wall thickness in mm	Working pressure in bar	Max. working pressure in bar	Burst pressure in bar	Tensile strength in kg
52	600	3.3	16	20	50	3900
65	750	3.3	16	20	50	6300
76	900	3.3	16	20	50	8800
90	1150	3.4	16	20	50	10900
102	1350	3.5	16	20	50	12400
114	1450	3.7	15	18	45	12400
127	1700	3.9	15	18	45	17000
152	1950	3.9	14	17	42	17900
180	2900	4.5	14	17	42	24000
205	3500	4.5	10	12	30	26900
254	4200	5.2	10	12	30	43200

 Specifications apply only to the hose. The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly.