

GH HILCOFLEX PU KULI

ROBUST, ELECTRICALLY CONDUCTIVE MULTI-PURPOSE HOSE MADE OF POLYURETHANE

MATERIAL CONSTRUCTION

Jacket lining:

- High-tenacity polyester yarn, circular woven
- Totally embedded in the rubber, offering optimum protection against damage
- Interwoven strands for electro-conductivity

Lining and jacket:

- Thermoplastic polyether polyurethane, extruded through the weave in a special one-step production process
- Electrical resistance less than 10^6 ohms
- Highly resistant to abrasion, 4–5 times longer service life than nitrile hoses
- Inside: Very smooth for minimal pressure loss
- Outside: Very smooth for good flexibility


ADVANTAGES

- ✓ Outstanding resistance to abrasion
- ✓ Extremely tough, hard-wearing and durable
- ✓ Resistant to oil, gasoline and chemicals (see resistance table)
- ✓ Resistant to aging and ozone
- ✓ More lightweight and flexible than mandrel-wound industrial hoses
- ✓ Stays flexible at cold temperatures

AT A GLANCE

Standard lengths

- 100 m

 Other lengths available on request (possibly with cutting fee)

Temperature ranges

-50 °C bis 75 °C

Standard colors

army green

Areas of application

- Refineries
 - Industry
 - Waste disposal
 - Military
 - Industrial and mine fire departments
 - Transporting oil, fuel and other flammable liquids
 - Ship refueling
 - Tank cleaning
 - Firefighting in mines and other potentially explosive areas
 - Powder extinguisher hose
-

PRESSURES

Working pressure:

Specifications apply only to the hose (medium water, 20 °C). The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly. For compressed air, the maximum working pressure is 25% of the burst pressure.

Maximum working pressure:

Approval can only be given by the manufacturer upon clarification of the exact area of application.

CONTACT

Gollmer & Hummel GmbH
Gässlesweg 23
75334 Straubenhardt

T +49 (0) 7082 9434-0

F +49 (0) 7082 9434-99

E info@gollmer-hummel.com

[Order hose sample >>](#)

DATASHEET

| Inside diameter in mm | Weight in g/m | Wall thickness in mm | Working pressure in bar | Max. working pressure in bar | Burst pressure in bar | Tensile strength in kg |
|-----------------------|---------------|----------------------|-------------------------|------------------------------|-----------------------|------------------------|
| 52 | 430 | 2.4 | 16 | 20 | 50 | 5,000 |
| 76 | 700 | 2.8 | 16 | 20 | 50 | 6,900 |
| 102 | 1150 | 3.3 | 16 | 20 | 50 | 13,800 |
| 127 | 1500 | 3.4 | 14 | 17 | 42 | 17,000 |
| 152 | 1900 | 3.7 | 14 | 17 | 42 | 17,900 |
| 205 | 3300 | 4.7 | 14 | 17 | 42 | 38,000 |

i Specifications apply only to the hose. The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly.