

GH HILCOFLEX PU TRAVELLER

DRAG HOSE FOR TRAVELLING IRRIGATORS / LATERAL IRRIGATION

MATERIAL CONSTRUCTION

Lining and Jacket:

- Polyurethane Thru-the-Weave Extrusion
- Specially designed linear and pivot irrigation systems. Small bending radius, high continuous working pressures, high tensile strength and very little elongation under pressure
- Totally embedded in the polyurethane, offering optimum protection against mechanical damage
- Thermoplastic polyether polyurethane, extruded through the weave in a special one-step production process
- Highly resistant to abrasion, 4–5 times longer service life than nitrile hoses
- Inside: Very smooth for minimal pressure loss
- · Outside: Very smooth for good flexibility

ADVANTAGES

- ✓ Very small bending radius, desgined for drag hose irrigations
- ✓ No kinking at low perssure
- ✓ Abrasion resistant
- ✓ Very flexible
- ✓ Small coil volume for easy handling
- ✓ It is five-times more abrasion resistant than conventional rubber hose

PRESSURES

Specifications apply only to the hose (medium water, 20 °C). The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly. For compressed air, the maximum working pressure is 25% of the burst pressure.

Order hose sample >>

AT A GLANCE

Temperature ranges

-50 °C bis 75 °C

(Specifications apply to Water)

Standard colors

blue

Areas of application

Lateral Irrigation

CONTACT

Gollmer & Hummel GmbH

Gässlesweg 23 75334 Straubenhardt

T +49 (0) 7082 9434-0

F +49 (0) 7082 9434-99

E info@gollmer-hummel.com

DATASHEET METRIC

| Inside diameter in mm | Weight in g/m | Wall thickness in mm | Working pressure in bar | Max. working pressure in bar | Burst pressure in bar | Tensile strength in kg |
|-----------------------------|---------------------|----------------------------|-------------------------------|---------------------------------------|-----------------------------|------------------------------|
| 76 | 800 | 2.7 | 13 | 16 | 40 | 4,500 |
| 90 | 900 | 2.8 | 13 | 16 | 40 | 6,000 |
| 102 | 1,000 | 3.2 | 13 | 16 | 40 | 7,000 |
| 114 | 1,300 | 3.4 | 12 | 15 | 35 | 9,000 |
| 127 | 1,500 | 3.6 | 12 | 15 | 35 | 12,000 |
| 152 | 1,800 | 4 | 12 | 15 | 35 | 14,000 |

i Specifications apply only to the hose. The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly.