

# GH HILCOFLEX PU TRAVELLER

## DRAG HOSE FOR TRAVELLING IRRIGATORS / LATERAL IRRIGATION

### MATERIAL CONSTRUCTION

#### Lining and Jacket:

- Polyurethane Thru-the-Weave Extrusion
- Specially designed linear and pivot irrigation systems. Small bending radius, high continuous working pressures, high tensile strength and very little elongation under pressure
- Totally embedded in the polyurethane, offering optimum protection against mechanical damage
- Thermoplastic polyether polyurethane, extruded through the weave in a special one-step production process
- Highly resistant to abrasion, 4-5 times longer service life than nitrile hoses
- Inside: Very smooth for minimal pressure loss
- Outside: Very smooth for good flexibility

### ADVANTAGES

- ✓ Abrasion resistant
- ✓ Very flexible
- ✓ Very small bending radius, designed for drag hose irrigators
- ✓ Small coil volume for easy handling
- ✓ It is five-times more abrasion resistant than conventional rubber hose

### PRESSURES

Specifications apply only to the hose (medium water, 20 °C). The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly. For compressed air, the maximum working pressure is 25% of the burst pressure.

[Order hose sample >>](#)

### AT A GLANCE

#### Temperature ranges

-50 °C bis 75 °C  
(Specifications apply to Water)

#### Standard colors

blue

#### Areas of application

- Lateral Irrigation

### CONTACT

Gollmer & Hummel GmbH  
Gässlesweg 23  
75334 Straubenhardt

**T** +49 (0) 7082 9434-0

**F** +49 (0) 7082 9434-99

**E** [info@gollmer-hummel.com](mailto:info@gollmer-hummel.com)

## DATASHEET

Inside diameter in mm	Weight in g/m	Wall thickness in mm	Burst pressure in bar	Tensile strength in kg
76	800	2.7	40	4,500
90	900	2.8	40	6,000
102	1000	3.2	40	7,000
127	1500	3.6	35	12,000
114	1300	3.4	35	9,000
152	1800	4.0	35	14,000

**i** Specifications apply only to the hose. The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly.