

# GH PROGRESS SPEZIAL

## HEAVY-DUTY FIRE HOSE WITH RUBBERIZED LINING AND JACKET

### MATERIAL CONSTRUCTION

#### Jacket lining:

- Warp: High-tenacity polyester
- Weft: Polyamide; circular woven, reinforced design
- The special jacket construction ensures outstanding adhesion and much lower pressure loss compared to a 100% polyester jacket lining
- Totally embedded in the rubber, offering optimum protection against mechanical damage

#### Rubberized lining and jacket:

- Very high-grade NBR/PVC rubber compound, extruded through the weave in a special one-step production process
- Special additives in the compound guarantee outstanding resistance to aging and ozone
- Inside: Very smooth for minimal pressure loss
- Outside: Wide, thick ribs for maximum abrasion resistance and excellent protection against contact heat

### ADVANTAGES

- ✓ Outstanding abrasion resistance, extremely tough and durable
- ✓ Resistant to oil, gasoline and chemicals (see resistance table)
- ✓ Extremely resistant to heat and flames
- ✓ Very low pressure loss, minimum elongation
- ✓ Resistant to aging and ozone
- ✓ Excellent adhesion between the rubber and jacket
- ✓ No cleaning or drying required

### AT A GLANCE

#### Temperature ranges

-20 °C bis 80 °C

(Specifications apply to Water)

---

#### Standard colors

yellow red

---

#### Areas of application

- Refineries
  - Chemical industry
  - Military
  - Airport fire departments
  - Industrial and municipal fire departments
  - Fire hose for the harshest conditions
- 

### CONTACT

**Gollmer & Hummel GmbH**  
Gässlesweg 23  
75334 Straubenhardt

**T** +49 (0) 7082 9434-0

**F** +49 (0) 7082 9434-99

**E** [info@gollmer-hummel.com](mailto:info@gollmer-hummel.com)

---

## PRESSURES

Pressure specifications apply only to the hose and not to pre-assembled hose lines with couplings!

[Order hose sample >>](#)

### DATASHEET **METRIC**

Inside diameter in mm	Weight in g/m	Wall thickness in mm	Working pressure in bar	Max. working pressure in bar	Burst pressure in bar	Tensile strength in kg	Approval
38	380	3.2	20	24	60	3,400	UL listed
45	460	3.3	20	24	60	4,000	UL listed
52	550	3.4	20	24	60	4,800	UL listed
65	750	3.7	20	24	60	6,900	UL listed
75	980	4	20	24	60	9,500	UL listed

**i** Specifications apply only to the hose. The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly.