

GH TEXFLEX AIR

SEMI-RIGID COMPRESSED AIR/LIGHTWEIGHT HOSE

MATERIAL CONSTRUCTION

Jacket:

- High-tenacity polyester yarn
- Monofilament coils in the weft keep hose semi-rigid
- Specially designed for high pressure and very tight bending radii

Lining:

Special, oil-resistant rubberized lining for compressed air

ADVANTAGES

- ✓ Exceptionally lightweight, anti-kinking and highly flexible (even at low temperatures)
- ✓ Designed for high continuous working pressure
- ✓ Very long single lengths available
- ✓ Very thin-walled – requires less space, easy to roll up on reels
- ✓ Excellent resistance to aging and ozone

PRESSURES

Working pressure:

Specifications apply only to the hose (medium water, 20 °C). The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly.

Maximum working pressure:

Approval can only be given by the manufacturer upon clarification of the exact area of application.

AT A GLANCE

Temperature ranges

-30 °C bis 80 °C

Standard colors

yellow

Areas of application

- Construction and industry
 - Lightweight compressed air hose for rolling on reels
-

CONTACT

Gollmer & Hummel GmbH
Gässlesweg 23
75334 Straubenhardt

T +49 (0) 7082 9434-0

F +49 (0) 7082 9434-99

E info@gollmer-hummel.com

Order hose sample >>

DATASHEET **METRIC**

Inside diameter in mm	Weight in g/m	Wall thickness in mm	Working pressure in bar	Burst pressure in bar
21	150	2	30	150
27	230	2	30	145

i Specifications apply only to the hose. The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly.