

GH TEXFLEX PU

SEMI-RIGID LIGHTWEIGHT HOSE FOR CONVEYING ABRASIVE MEDIA

MATERIAL CONSTRUCTION

Jacket:

- High-tenacity polyester yarn, spun-dyed, circular woven
- Monofilament coils in the weft keep hose semi-rigid
- Special design for high pressure and very tight bending radii

Lining:

- Polyurethane

ADVANTAGES

- ✓ Exceptionally lightweight, anti-kinking and highly flexible (even at low temperatures)
- ✓ Designed for high continuous working pressure
- ✓ Easy to roll up on reels
- ✓ Excellent abrasion resistance

PRESSURES

Working pressure:

Specifications apply only to the hose (medium water, 20 °C). The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly.

Maximum working pressure:

Approval can only be given by the manufacturer upon clarification of the exact area of application.

AT A GLANCE

Temperature ranges

-20 °C bis 60 °C

Standard colors

yellow / orange

Areas of application

- Concrete and mortar hose
 - Construction industry
-

CONTACT

Gollmer & Hummel GmbH
Gässlesweg 23
75334 Straubenhardt

T +49 (0) 7082 9434-0

F +49 (0) 7082 9434-99

E info@gollmer-hummel.com

Order hose sample >>

DATASHEET

Inside diameter in mm	Weight in g/m	Burst pressure in bar
25	270	120

i Specifications apply only to the hose. The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly.