

# GH THUNDERSNOW

## SINGLE JACKET SNOW CANNON HOSE

### MATERIAL CONSTRUCTION

#### Jacket:

- High-tenacity polyester yarn, circular woven in twill weave
- Single jacket construction, excellent pressure resistance yet lightweight and flexible

#### Lining:

- High-grade EPDM rubber, specially designed to be flexible at low temperatures
- Co-extruded adhesive layer, penetrates the weave almost completely during steam vulcanization
- Excellent adhesion between the rubber and jacket, very smooth for minimal pressure loss
- Reinforced design to eliminate coupling binding leaks

### ADVANTAGES

- ✓ High continuous working pressure, sufficient reserves for pressure peaks
- ✓ Good visibility in snow, even in twilight
- ✓ Highly resistant to abrasion, tough and durable
- ✓ Outstanding resistance to aging, UV and ozone
- ✓ Stays flexible at cold temperatures
- ✓ Resistant to mildew and rot

### PRESSURES

In accordance with EN ISO 7751 specifications for water. Please note that for compressed air a minimum ratio of 1:4 must be maintained between the working pressure and the burst pressure. Operating pressure specifications apply only to hose lines with couplings extruded by us – otherwise only to the hose.

[Order hose sample >>](#)

### AT A GLANCE

#### Temperature ranges

-40 °C bis 80 °C

(Specifications apply to Water)

---

#### Standard colors

yellow

---

#### Areas of application

- Feeder hose for snow-making systems
- 

### CONTACT

**Gollmer & Hummel GmbH**  
Gässlesweg 23  
75334 Straubenhardt

**T** +49 (0) 7082 9434-0

**F** +49 (0) 7082 9434-99

**E** [info@gollmer-hummel.com](mailto:info@gollmer-hummel.com)

---

## DATASHEET

Inside diameter in mm	Weight in g/m	Working pressure in bar	Burst pressure in bar
52	450	60	120

**i** Specifications apply only to the hose. The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly.