

# GH TITAN COMBAT NEON

## BEST FABRIC TYPE 1 FIRE HOSE IN ITS CLASS WITH INNER CORE OF EPDM RUBBER

### MATERIAL CONSTRUCTION

The combination of special rubber, the GH 4Z system and flatline vulcanization ensures much greater flexibility and ideal suitability for hose carrying baskets and hose packs.

### ADVANTAGES

- ✓ Small bending radius resulting in less kinking
- ✓ Longer lifespan + higher flow rates
- ✓ Better abrasion resistance due to special G&H 4Z system, well above standard requirements
- ✓ High burst pressures for high performance reserves
- ✓ High-grade, smooth EPDM rubber lining with excellent resistance to foaming agents/chemicals
- ✓ Supple, flexible properties
- ✓ Made from high-tenacity, spun-dyed polyester
- ✓ Colorfast

### PRESSURES

#### Working pressure:

Specifications apply only to the hose (medium water, 20 °C). The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly.

#### Maximum working pressure:

Approval can only be given by the manufacturer upon clarification of the exact area of application.

### AT A GLANCE

#### Temperature ranges

-40 °C bis 80 °C

(Specifications apply to Water)

#### Standard colors

neon yellow

#### Areas of application

- Fire department
- Industry
- Military
- Disaster relief

### CONTACT

Gollmer & Hummel GmbH  
Gässlesweg 23  
75334 Straubenhardt

**T** +49 (0) 7082 9434-0

**F** +49 (0) 7082 9434-99

**E** [info@gollmer-hummel.com](mailto:info@gollmer-hummel.com)

**Order hose sample >>**

## DATASHEET

Inside diameter in mm	Weight in g/m	Working pressure in bar	Burst pressure in bar	Bending radius in mm	DIN performance level	Approval
42	240	16	75	330	L2	DIN 14811
52	310	16	75	375	L2	DIN 14811
75	460	16	75	600	L3	DIN 14811

**i** Specifications apply only to the hose. The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly.

## PRODUCT IMAGES

