

GH TITAN REEL

UNCOATED LAYFLAT HOSE FOR WALL HYDRANTS ACCORDING TO DIN EN 14540

MATERIAL CONSTRUCTION

Jacket:

- High-tenacity polyester yarn, circular woven in twill weave (much more resistant to abrasion than plain weave)
- 2-ply warp threads, lightweight, tough and flexible

Lining:

- High-grade EPDM rubber, flexible at low temperatures, also suitable for hot water, wall thickness 0.8 mm
- Excellent resistance to seawater, chemicals, UV radiation and ozone (much better than SBR, for example)
- Co-extruded adhesive layer (0.2 mm wall thickness), penetrates the weave almost completely during vulcanization
- This type of rubber guarantees a very smooth lining with low friction loss and excellent adhesion between the rubber and jacket


ADVANTAGES

- ✓ Very lightweight and highly flexible (also at extremely low temperatures)
- ✓ Small coil diameter
- ✓ Excellent resistance to aging and ozone
- ✓ Lining extremely resistant to seawater and a wide range of chemicals (see resistance table)
- ✓ Resistant to mildew and rot
- ✓ Easy to repair

AT A GLANCE

Standard lengths

- 100 m

 Other lengths available on request (possibly with cutting fee)

Temperature ranges

-40 °C bis 80 °C

(Specifications apply to Water)

Standard colors

white

Areas of application

- Wall hydrants according to DIN EN 14540

CONTACT

Gollmer & Hummel GmbH
Gässlesweg 23
75334 Straubenhardt

T +49 (0) 7082 9434-0

F +49 (0) 7082 9434-99

E info@gollmer-hummel.com

PRESSURES

Working pressure:

Specifications apply only to the hose (medium water, 20 °C). The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly.

Maximum working pressure:

Approval can only be given by the manufacturer upon clarification of the exact area of application.

[Order hose sample >>](#)

DATASHEET

Inside diameter in mm	Weight in g/m	Burst pressure in bar	Approval
42	215	50	EN 14540
52	260	50	EN 14540

i Specifications apply only to the hose. The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly.