

GH TITAN X-TREME GELB

INDOOR ATTACK TYPE 1 FIRE HOSE FOR THE TOUGHEST REQUIREMENTS, CONFORMS TO DIN 14811 PERFORMANCE LEVEL 3

MATERIAL CONSTRUCTION

The combination of special rubber, the GH 4Z system and flatline vulcanization ensures much greater flexibility and ideal suitability for hose carrying baskets and hose packs.

- High-grade EPDM rubber lining, flexible at low temperatures, also suitable for hot water
- This type of rubber guarantees a very smooth lining with low friction loss
- Very good adhesion between the rubber and jacket

ADVANTAGES

- ✓ Burst pressure over 80 bar for high performance reserves
- ✓ Very small bending radius resulting in less kinking = longer lifespan
- ✓ The perfect C-hose for indoor firefighting
- ✓ Extremely high abrasion resistance thanks to special G&H 4Z system
- ✓ Distinctive design with contrasting weave for high visibility in indoor firefighting
- ✓ Clearly exceeds Level 3 requirements (DIN 14811/A2) for abrasion
- ✓ Standard G&H HOSE GUARD protects against coupling defects
- ✓ Stainless-steel wire hose binding
- ✓ Less susceptible to tangling and stretching
- ✓ Suitable for all types of hose washing systems
- ✓ High-grade EPDM rubber lining, flexible at low temperatures, also suitable for hot water
- ✓ This type of rubber lining guarantees a very smooth lining with low friction loss
- ✓ Very good adhesion between the rubber and jacket

AT A GLANCE

Temperature ranges

-40 °C bis 80 °C

(Specifications apply to Water)

Standard colors

yellow

Areas of application

- Fire department
- Industry
- Military
- Disaster relief

CONTACT

Gollmer & Hummel GmbH
Gässlesweg 23
75334 Straubenhardt

T +49 (0) 7082 9434-0

F +49 (0) 7082 9434-99

E info@gollmer-hummel.com

PRESSURES

Working pressure:

Specifications apply only to the hose (medium water, 20 °C). The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly.


Maximum working pressure:

Approval can only be given by the manufacturer upon clarification of the exact area of application.

Order hose sample >>

DATASHEET METRIC

Inside diameter in mm	Weight in g/m	Working pressure in bar	Burst pressure in bar	Bending radius in mm	DIN performance level	Approval
25	160	16	100	150		DIN 14811
38	240	16	90			
42	265	16	85	220	L3	DIN 14811
45	310	16	100			
52	330	16	90	300	L3	DIN 14811
70	530	16	80			
75	545	16	80	450	L3	DIN 14811
110	810	16	55			DIN 14811

 Specifications apply only to the hose. The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly.