

GH HOSE PACK

the hose package carrying system

SYSTEMATIC CARRYING. FLEXIBLE USE.

Effective hose management is one of the key factors for success in firefighting operations. It not only influences the speed and efficiency of firefighting, but also has a significant impact on the safety of the emergency services.

With the GH HOSE PACK, a modern hose package carrying system, the transport and handling of hose packages is much more structured and faster than with conventional hose laying.

Lightweight on the shoulder or comfortable to hold by the handle, the hose package can be placed directly at the smoke line without laborious removal – including the nozzle.

Tactically flexible, the system is ideal for various operational scenarios such as indoor attacks, high-rise fires or industrial facilities.



HIGHLIGHTS

- For all standard fire hoses
- Velcro straps for easy opening and closing
- Can be opened using disposable cable ties on additional eyelets
- Comfortable rubber handle
- Reusable in two sizes
- GH HOSE PACK '15 fits into a carrying basket



GH HOSE PACK '30

for hose lengths of 20–60 m

Strap width: 50 mm

Handle width: 130 mm

Weight: 740 g



GH HOSE PACK '15


for hose lengths of 5–15 m

Strap width: 50 mm

Handle width: 130 mm

Weight: 480 g

Shoulder strap length: 450 mm



BLOW UP OR LAY OUT FIRST – WITH THE GH HOSE PACK, YOU CAN DO BOTH

The Velcro straps make it easy to open and close the system.

Disposable cable ties can be attached to the eyelets provided, which are attached to the Velcro straps for inserting the hose. These can be automatically blown up at a pressure of approx. 4–5 bar. This eliminates the need to open the Velcro straps manually. The hose unfolds itself in even the tightest of spaces in neat loops – without knots, kinks or trip hazards, but in a controlled, targeted and time-saving manner. Maximum freedom for every tactic, adapted to the situation.



Thanks to the resealable Velcro straps, each individual hose can be adjusted to the desired size and to additional accessories (e.g. shut-off device or hollow jet pipe).

The standard model, our **GH HOSE PACK '30'**, has 5 Velcro straps and is suitable for hose lengths from 20 m to 60 m (C42 hoses up to 60 m; B75 turntable ladder hose up to 35 m).



The **GH HOSE PACK '15'** is brand new and features 3 Velcro straps for hose lengths from 5 m to 15 m. This model is equipped with a carrying strap for additional comfort.



The eyelets can also be ordered separately as a set of 5 if you wish to continue using your existing GH HOSE PACK carrying system.



RETROFIT KIT:

- 5 metal eyelets
- 3 metal eyelets

When selecting cable ties, we at Gollmer & Hummel recommend a material width of 3.5 mm to 4.0 mm. If cable ties with a material thickness of more than 4 mm are used, we accept no liability for any resulting damage to the system and hose.