

GH HOSE PACK CARRYING SYSTEM

The new **GH HOSE PACK CARRYING SYSTEM** is even more easy to handle and therefore also very practical for transporting hose packages. The individual Metal lugs, which previously had to be attached to the loops of the Velcro tape, are new. With the new system, the two eyelets are now connected with a disposable cable tie. This eliminates the need to manually open the Velcro straps before pressure is applied to the hose. The carrying system can be opened immediately (the cable ties open at approx. 4-5 bar). The Velcro straps allow each individual strap to be adjusted to the size required. (Such as shut-off device, hollow jet pipe, C 42 hoses up to 60m). The Metal lugs can also be ordered separately as a set of 10 if you want to upgrade your existing GH HOSE PACK CARRYING SYSTEM.

We recommend a material thickness (width) of 3,5 - 4,0 mm of the cable tie. We would also ask for your understanding that we can't accept any liability for damage to the system if cable ties with a material thickness (width) of more than 4 mm are used with the system.

HIGHLIGHTS:

- comfortable rubber handle
- quickly fixed with cable ties
- suitable for all standard fire hoses
- Velcro straps do not need to be loosened
- Velcro fastener can always be retightened

TECHNICAL DATA:	
Belt width:	50 mm
Handle width:	130 mm
Weight:	740 g

ACCESSORIES included in the first set:

- 10 Metal lugs
- REPLACEMENT KIT: • 5 Metal lugs

